

Projector

Sharp/ NEC P525UL Projector



- No filter service required – a completely sealed optical laser LCD engine allows a filter-free design and brilliant colour brightness is maintained.
- No lamp replacement – up to 20,000 h maintenance free operation possible due to Laser Light Source.
- Professional and Flexible Installation – versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.
- Low Noise Level – with 22dB*, the silent technology will not disturb your meeting.
- Risk Group 2 – because of the Risk Group 2 compliance, no prescribed safety precautions are necessary.

Specifications

PANEL RESOLUTION

1-Chip DLP(TI) / 3-Chip DLP(TI) / 3-LCD-Panel - / - / •
Native Resolution 1920 x 1200 (WUXGA)

VIDEO TERMINALS

HDMI •

AUDIO TERMINALS

RCA-Stereo Terminal In/Out •

PICTURE DATA

Luminance ECO-mode (ANSI Lumen) / Standard (ANSI Lumen) 5000 ANSI Lumen (approx. 60% in Eco Mode)
Contrast 500000:1
Fan 22 dB ECO / 24 dB Standard
Lens built-in / Changeable Lens - / •
Zoom-Lens (Manual/ Motorized) • / -
Lens Shift (H/V) • / •
Keystone (manual/auto) • / -

OTHERS

Power supply (V) / power consumption, standard (W) / power consumption, ECO (W) / stand-by (W) 100 - 240 / 320 / 238 / 0.3
Dimensions in mm (W x H x D) 480 x 122 x 407
Weight (kg) 9.7

DATA TERMINALS

HDMI •
15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr) •

CONTROL TERMINALS

RS232C (Sub-D) •
LAN •
USB-Host •

COLOUR STANDARDS

PAL 60/N/M • / • / •
SECAM •
NTSC (MHz) 3.58/ 4.43 • / •

ACCESSORIES

Remote Control / Owners Manual (CD-ROM) • / •
Power Cable / PC Cable • / -