

Projector

Sharp / NEC P603X Projector



- Professional and Flexible Installation – versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.
- High brightness – for best performance in bright ambient light.
- Minimized cost of ownership – due to long lamp life and filter exchange intervals.
- Peace of Mind – with future-proof connectivity.
- Cost effective replacement – of existing NEC P model installations to achieve better imaging for lectures and presentations without wall-mount adjustment.

Specifications

PANEL RESOLUTION

1-Chip DLP(TI) / 3-Chip DLP(TI) / 3-LCD-Panel	- / - / •
Native Resolution	1024 x 768 (XGA)
XGA 1.024 x 768	•

DATA TERMINALS

HDMI	•
15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr)	•

CONTROL TERMINALS

RS232C (Sub-D)	•
----------------	---

COLOUR STANDARDS

PAL 60/N/M	• / • / •
SECAM	•
NTSC (MHz) 3.58/ 4.43	• / •

ACCESSORIES

Remote Control / Owners Manual (CD-ROM)	• / •
Power Cable / PC Cable	• / -

PC-INPUT

H-Frequency (kHz)	15 - 100 KHz
V-Frequency (Hz)	50 - 120 Hz

VIDEO TERMINALS

S-Video (Y/C)	•
HDMI	•

AUDIO TERMINALS

Mini Jack (3.5 mm) In/Out	•
RCA-Stereo Terminal In/Out	•
Via HDMI-Terminal	•

PICTURE DATA

Luminance ECO-mode (ANSI Lumen) / Standard (ANSI Lumen)	3600 / 6000
Contrast	20000:1
Projection lamp (W) / Lamp lifetime ECO-Mode (h) / Lamplife Standard (h)	330 / 8000 / 4000
Fan	34 dB ECO / 37 dB
Lens built-In / Changeable Lens	- / •
Zoom-Lens (Manual/ Motorized)	• / -
Lens Shift (H/V)	• / •
Keystone (manual/auto)	• / -

OTHERS

Power supply (V) / power consumption, standard (W) / power consumption, ECO (W) / stand-by (W)	100-240 / 414 / 258 / 0.2
Dimensions in mm (W x H x D)	420 x 133 x 322
Weight (kg)	4.7