

Projector

Sharp/ NEC P605UL Projector



- No filter service required – a completely sealed optical laser LCD engine allows a filter-free design and brilliant colour brightness is maintained.
- Future-proof input management – thanks to 4K@30 Hz input processing.
- Risk Group 2 – because of the Risk Group 2 compliance, no prescribed safety precautions are necessary.
- Low Noise Level – with 19dB*, the silent technology will not disturb your meeting.
- No lamp replacement – up to 20,000 h maintenance free operation possible due to Laser Light Source.

Specifications

PANEL RESOLUTION

1-Chip DLP(TI) / 3-Chip DLP(TI) / 3-LCD-Panel - / - / •
Native Resolution 1920 x 1200 (WUXGA)

VIDEO TERMINALS

HDMI •

AUDIO TERMINALS

Mini Jack (3.5 mm) In/Out •
Via HDMI-Terminal •

PICTURE DATA

Luminance ECO-mode (ANSI Lumen) / Standard (ANSI Lumen) 6000
Contrast 600000:1
Projection lamp (W) / Lamp lifetime ECO-Mode (h) / Lamplife Standard (h) 20000 2
Fan 19 dB ECO / 25 dB
Lens built-in / Changeable Lens - / •
Zoom-Lens (Manual/ Motorized) • / -
Lens Shift (H/V) • / •
Keystone (manual/auto) • / -

OTHERS

Power supply (V) / power consumption, standard (W) / power consumption, ECO (W) / stand-by (W) 100-240 / 357 / 257 / 0.3
Dimensions in mm (W x H x D) 480 x 122 x 407
Weight (kg) 9.7

DATA TERMINALS

HDMI •
15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr) •

CONTROL TERMINALS

RS232C (Sub-D) •
LAN •
USB-Host •

COLOUR STANDARDS

PAL 60/N/M • / • / •
SECAM •
NTSC (MHz) 3.58/ 4.43 • / •

ACCESSORIES

Remote Control / Owners Manual (CD-ROM) • / •
Power Cable / PC Cable • / -